

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
13 May 2004 (13.05.2004)

PCT

(10) International Publication Number
WO 2004/039553 A1

(51) International Patent Classification⁷: **B29C 31/04**,
43/34

[IT/IT]; Via 2 Agosto 1980, 8, I-40023 Castel Guelfo (IT).
PARRINELLO, Fiorenzo [IT/IT]; Via Zanardi, 122/A,
I-40059 Medicina (IT).

(21) International Application Number:
PCT/EP2003/004214

(74) Agent: **MODIANO, Guido**; Modiano & Associati, Via
Meravigli, 16, I-20123 Milano (IT).

(22) International Filing Date: 23 April 2003 (23.04.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
BO2002A000683 31 October 2002 (31.10.2002) IT

(71) Applicant (for all designated States except US): **SACMI
COOPERATIVA MECCANICI IMOLA S.C.R.L.**
[IT/IT]; Via Provinciale Selice, 17/A, I-40026 Imola (IT).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN,
YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

(72) Inventors; and

(75) Inventors/Applicants (for US only): **PUCCI, Fabrizio**

[Continued on next page]

(54) Title: DEVICE FOR REMOVING DOSES OF PLASTIC MATERIAL FROM AN EXTRUDER



(57) Abstract: A device for removing doses of plastic material from the outflow orifice of an extruder (23) by means of at least one removal element (8) movable with respect to the extruder and provided with a receptacle (15) for a dose (6) removed from the orifice, the removal element (8) comprising a severing element (14) adapted to cut into the plastic material dispensed by the extruder (23) along a severing edge (14a) advancing through the material to from one side of the orifice (24b) to the other, the receptacle (15) being shaped so as to accommodate the dose (6) and allow its expulsion substantially in the direction of the severing edge (14a).

WO 2004/039553 A1

WO 2004/039553 A1



SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*